

PEA-M SERIES

POWER INVERTER



Type				Inverter Heat Pump				
Indoor Unit				PEA-M200LA		PEA-M250LA		
Outdoor Unit				PUZ-ZM200YKA		PUZ-ZM250YKA		
Refrigerant				R32*1				
Power Supply	Source			Separate power supply				
	Outdoor (V/Phase/Hz)			400 / Three / 50				
Cooling	Capacity	Rated	kW	19.0		22.0		
		Min - Max	kW	9.2 - 22.4		9.9 - 27.0		
	Total Input	Rated	kW	5.757		7.213		
	EER			3.30		3.05		
		EEL Rank		-		-		
Heating (Average Season)	Capacity	Rated	kW	22.4		27.0		
		Min - Max	kW	7.1 - 25.0		7.3 - 31.0		
	Total Input	Rated	kW	6.400		7.941		
	COP			3.50		3.40		
		EEL Rank		-		-		
Operating Current (max)				25.7		25.9		
Indoor Unit	Input [Cooling / Heating]	Rated	kW	0.35 / 0.35		0.53 / 0.53		
	Operating Current (max)		A	3.1		3.4		
	Dimensions	H x W x D	mm	470 - 1370 - 1120				
	Weight		kg	87				
	Air Volume [Lo-Mid-Hi]		m³/min	42 - 51 - 60 (60Pa - 150Pa) 42 - 51 - 55 (200Pa)		50 - 61 - 72 (60Pa - 100Pa) 45 - 55 - 65 (150Pa) 45 - 50 - 55 (200Pa)		
	External Static Pressure		Pa	(60) / 75 / (100) / (150) / (200)				
	Sound Level (SPL) [Lo-Mid-Hi]		dB(A)	35 - 40 - 43		38 - 43 - 47		
	Sound Level (PWL)		dB(A)	63 - 64 - 64		67 - 67 - 68		
	Dimensions	H x W x D	mm	1338 - 1050 - 330 (+40)				
Outdoor Unit	Weight		kg	137		138		
	Air Volume	Cooling	m³/min	140		140		
		Heating	m³/min	140		140		
	Sound Level (SPL)	Cooling	dB(A)	59		59		
		Heating	dB(A)	62		62		
	Sound Level (PWL)	Cooling	dB(A)	77		77		
	Operating Current (max)		A	22.5		22.5		
	Breaker Size		A	32		32		
	Ext. Piping	Diameter	Liquid / Gas	mm	9.52 / 25.4		12.7 / 25.4	
		Max. Length	Out-In	m	100		100	
	Max. Height	Out-In	m	30		30		
Guaranteed Operating Range [Outdoor]		Cooling *2	°C	-15 ~ +46		-15 ~ +46		
		Heating	°C	-20 ~ +21		-20 ~ +21		

*1 Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

*2 Optional air protection guide is required where ambient temperature is lower than -5°C.

PEA-M SERIES

STANDARD INVERTER



Type			Inverter Heat Pump					
Indoor Unit			PEA-M200LA		PEA-M250LA			
Outdoor Unit			PUZ-M200YKA		PUZ-M250YKA			
Refrigerant			R32*1					
Power Supply	Source		Separate power supply					
	Outdoor (V/Phase/Hz)		400 / Three / 50					
Cooling	Capacity	Rated	kW	19.0		22.0		
		Min - Max	kW	9.2 - 22.4		9.9 - 27.0		
	Total Input	Rated	kW	6.089		7.333		
	EER			3.12		3.00		
		EEL Rank		-		-		
Heating (Average Season)	Capacity	Rated	kW	22.4		27.0		
		Min - Max	kW	6.8 - 25.0		7.3 - 31.0		
	Total Input	Rated	kW	6.588		8.181		
	COP			3.40		3.30		
		EEL Rank		-		-		
Operating Current (max)			25.7		25.9			
Indoor Unit	Input [Cooling / Heating]	Rated	kW	0.35 / 0.35		0.53 / 0.53		
	Operating Current (max)		A	3.1		3.4		
	Dimensions	H x W x D	mm	470 - 1370 - 1120				
	Weight		kg	87				
	Air Volume [Lo-Mid-Hi]		m³/min	42 - 51 - 60 (60Pa - 150Pa)	42 - 51 - 55 (200Pa)	50 - 61 - 72 (60Pa - 100Pa)	45 - 55 - 65 (150Pa) 45 - 50 - 55 (200Pa)	
	External Static Pressure		Pa	(60) / 75 / (100) / (150) / (200)				
	Sound Level (SPL) [Lo-Mid-Hi]		dB(A)	35 - 40 - 43		38 - 43 - 47		
	Sound Level (PWL)		dB(A)	63 - 64 - 64		67 - 67 - 68		
	Dimensions	H x W x D	mm	1338 - 1050 - 330 (+40)				
	Weight		kg	129		138		
Outdoor Unit	Air Volume	Cooling	m³/min	140		140		
		Heating	m³/min	140		140		
	Sound Level (SPL)	Cooling	dB(A)	58		59		
		Heating	dB(A)	60		62		
	Sound Level (PWL)	Cooling	dB(A)	78		77		
	Operating Current (max)		A	22.5		22.5		
	Breaker Size		A	32		32		
	Ext. Piping	Diameter	Liquid / Gas	mm	9.52 / 25.4		12.7 / 25.4	
		Max. Length	Out-In	m	70		70	
		Max. Height	Out-In	m	30		30	
Guaranteed Operating Range [Outdoor]		Cooling*2	°C	-15 ~ +46		-15 ~ +46		
		Heating	°C	-20 ~ +21		-20 ~ +21		

*1 Refrigerant leakage contributes to climate change. Refrigerant with lower global warming potential (GWP) would contribute less to global warming than a refrigerant with higher GWP, if leaked to the atmosphere. This appliance contains a refrigerant fluid with a GWP equal to 1975. This means that if 1 kg of this refrigerant fluid would be leaked to the atmosphere, the impact on global warming would be 1975 times higher than 1 kg of CO₂, over a period of 100 years. Never try to interfere with the refrigerant circuit yourself or disassemble the product yourself and always ask a professional.

*2 Optional air protection guide is required where ambient temperature is lower than -5°C.